

TECHNICAL SPECIFICATIONS

| Feature | Unit | Minimum limit | Standard | Maximum limit |
|---------------|----------------------|---------------|----------|---------------|
| Grams/meter | g/sq.m | 450 | 500 | 550 |
| Width | inches | 42 | 44 | *** |
| Cutable width | inches | 40 | 42 | *** |
| Fabric Yield | m/kg | 1.56 | 1.80 | 2.11 |
| Ounces/yards | Oz/sq.yd | 13.3 | 14.8 | 16.2 |
| Fiber content | 98% NYLON 2% SPANDEX | | | |

Certifications



Additional comments about technical specifications

Larger width is not considered to be out of specification.

REST TIME 24 HOURS.

Style subject to crease marks.

NCM

| PFD | Off White/White | Dyed | Printed |
|------------|-----------------|------------|------------|
| 6006.31.10 | 6006.31.10 | 6006.32.10 | 6006.34.10 |

DIMENSIONAL STABILITY

| Shrinkage after washing (Machine wash - dry flat %) | Length (%) | Width (%) |
|-----------------------------------------------------|------------|-----------|
| | 5 | 5 |

Additional comments about dimensional stability

The shrinkage value is an average between the batches produced and may be subject to change.

Do not leave dirty clothes together in a closed place for a long time, always keep separated in a cool and ventilated place.

Separate by light and dark colors. Use neutral soap. Do not twist.

WASHING INSTRUCTIONS



- maximum temperature for the machine wash 40C (105F) / delicate gentle



- do not bleach



- dry flat



- do not iron



- dryclean, any solvent, mild cycle

Note - Note - The symbols should appear in the following order: washing, bleaching, drying, ironing and professional dry cleaning.

STORAGE INSTRUCTIONS

- Do not hit the ends of the fabric (do not hit the top).
- Keep the packaging of the rolls until their end use.
- The identification of the rolls must always be kept.
- Stored textiles should not be exposed to the light. The exposure will compromise the fabric over time.
- Separate by batch.

GENERAL COMMENTS

- Neon colors have low resistance to light and washing; they should not be mixed with other colors and / or fabric in the same piece; they should be washed separately.
- The washing mode is performed on the fabric, but after the fabric is converted into clothing, it must be evaluated (clothing appearance, use of other fabrics, use of interfacing / interlinings, etc).
- Be careful of the fabric getting in contact with abrasive surfaces, yarn may be tugged.
- Do not mix batches.
- Claims will be accepted within 15 days after receipt of the goods.
- All tests mentioned above were performed through NBR, ISO, AATCC standards and / or internal standards.

Prepared by Andreia: Quality / Kalimo
Approved by Murilo: Technical Manager