

### TECHNICAL SPECIFICATIONS

| Feature        | Unit                  | Minimum limit | Standard | Maximum limit |
|----------------|-----------------------|---------------|----------|---------------|
| Grams/meter    | g/sq.m                | 248           | 275      | 303           |
| Width          | inches                | 43            | 45       | ***           |
| Cuttable width | inches                | 41            | 43       | ***           |
| Fabric Yield   | m/kg                  | 2.74          | 3.16     | 3.70          |
| Ounces/yards   | Oz/sq.yd              | 7.3           | 8.1      | 8.9           |
| Fiber content  | 90% NYLON 10% SPANDEX |               |          |               |

#### Certifications



#### Additional comments about technical specifications

Larger width is not considered to be out of specification.

REST TIME 24 HOURS.

#### NCM

| PFD        | Off White/White | Dyed       | Printed    |
|------------|-----------------|------------|------------|
| 6004.10.31 | 6004.10.31      | 6004.10.32 | 6004.10.34 |

### DIMENSIONAL STABILITY

| Shrinkage after washing (Hand wash - hang to dry %) | Length (%) | Width (%) |
|---|------------|-----------|
|   | 5          | 12        |

#### Additional comments about dimensional stability

The shrinkage value is an average between the batches produced and may be subject to change.

Do not leave dirty clothes together in a closed place for a long time, always keep separated in a cool and ventilated place.

Separate by light and dark colors. Use neutral soap. Do not twist.

### WASHING INSTRUCTIONS



- hand wash



- do not bleach



- hang to dry



- do not iron



- do not dryclean

Note - The symbols should appear in the following order: washing, bleaching, drying, ironing and professional dry cleaning.

### STORAGE INSTRUCTIONS

- Do not hit the ends of the fabric (do not hit the top).
- Keep the packaging of the rolls until their end use.
- The identification of the rolls must always be kept.
- Stored textiles should not be exposed to the light. The exposure will compromise the fabric over time.
- Separate by batch.

### GENERAL COMMENTS

- Neon colors have low resistance to light and washing; they should not be mixed with other colors and / or fabric in the same piece; they should be washed separately.
- The washing mode is performed on the fabric, but after the fabric is converted into clothing, it must be evaluated (clothing appearance, use of other fabrics, use of interfacing / interlinings, etc).
- Be careful of the fabric getting in contact with abrasive surfaces, yarn may be tugged.
- Do not mix batches.
- Claims will be accepted within 15 days after receipt of the goods.
- All tests mentioned above were performed through NBR, ISO, AATCC standards and / or internal standards.

Prepared by Sara Almeida: Quality / Kalimo  
Approved by Murilo Garcia: Technical Manager